



AUSTRALIAN DESIGNED ENGINEERED WITH EXPERIENCE



R32 GAS3X MORE GREEN-HOUSE FRIENDLY



BLUEFIN COATING ANTI-CORROSION



TITANIUM CORROSION RESISTANT HEAT EXCHANGER



SMART TECH AUTOMATIC OPERATION



LESS THAN 57 DECIBELS SUPER QUIET



270° AIR INTAKEOPTIMAL AIR FLOW

TDI ULTRA INVERTER HEAT PUMP



KEEP TURNING UP THE HEAT!

Spend more time in the pool with the whole family. Efficient pool heating and everyday swimming gives you more opportunities to create special memories with those you love. Dive in, laugh and play... together.

WHY A TOP DISCHARGE INVERTER HEAT PUMP?

The vertical exhaust TDI Ultra is the most practical solution for pool owners with space constraints. The innovative design, with 270° air intake, ensures the heat pump can be installed in almost any application; without compromising on performance or operating efficiency.



TDI ULTRA INVERTER **HEAT PUMP SPECIFICATIONS**



| | TDI 13 | TDI 20 | TDI 26 |
|--|-------------------------|------------|------------|
| Heating Condition #1 : Ambient 26 °C, Inlet/Outlet: 26/28 °C, Humidity 80% | | | |
| Heating capacity (kW) | 12.56 | 20.41 | 26.21 |
| Power Input (kW) | 0.18~1.95 | 0.27~3.28 | 0.37~4.10 |
| C.O.P. | 14.65~6.46 | 14.35~6.23 | 14.35~6.54 |
| Heating Condition #2 : Ambient 15°C, Inlet/Outlet: 26/28°C, Humidity 70% | | | |
| Heating capacity (kW) | 9.75 | 15 | 19.5 |
| Power Input (kW) | 0.25~1.91 | 0.37~2.96 | 0.53~3.83 |
| C.O.P. | 8.2~5.11 | 8.17~5.08 | 8.2~5.1 |
| General Info | | | |
| Max Current (A) | 12 | 18 | 24 |
| Max Power Input (kW) | 3.2 | 4.7 | 6.33 |
| Controller | LED | LED | LED |
| Water Temp. Heating Mode (°C) | 40 | | |
| Water Temp. Cooling Mode (°C) | 8~28 | | |
| Running Ambient Temp. (°C) | -10-43 | | |
| Refrigerant | R32 | | |
| Compressor Brand | Mitsubishi | | |
| Gas Control | EEV | | |
| 4-Way Valve | Yes | | |
| Heat Exchanger | Titanium in PVC | | |
| Water Pipe Connection (mm) | 40/50 | | |
| Fan Type | Vertical | | |
| Water Flow LPM (Litres Per Minute) | 75 | 110 | 145 |
| Noise Level at 1m dB(A) | 42~53 | 45~55 | 45~57 |
| Net Dimension (mm) | 500x500x720 640x640x800 | | |

The values indicated are valid under ideal conditions. Pool covered with a thermal cover, heating system available to run up to 16 hours per day.

The most efficient way to prevent heat loss, keep your pool clean and save on heating, chemicals and maintenance.

CONTROL FROM YOUR **SMARTPHONE**





Slacks Creek, Qld T: (07) 3299 2700 Australia 4127

U 17, 6 Maunder St 1800 243 887 F: (07) 3299 2800